

Fiat Rear Camber /Toe Shim pack

1. Perform pre-inspection, checking for loose or worn parts.
2. Perform complete alignment check to determine the alignment need.
3. Raise the rear of the vehicle and support securely.
4. Remove tire and wheel assembly.
5. Loosen the four wheel hub bolts.
6. Choose the correct option for camber/toe shim(s) to achieve proper alignment.
7. Install shim(s) behind the backing plate and evenly torque hub bolts to manufacturer's specification.
8. Reinstall tire assembly and finish alignment.



95-296-0114

Fiat Rear Camber /Toe Shim pack

1. Perform pre-inspection, checking for loose or worn parts.
2. Perform complete alignment check to determine the alignment need.
3. Raise the rear of the vehicle and support securely.
4. Remove tire and wheel assembly.
5. Loosen the four wheel hub bolts.
6. Choose the correct option for camber/toe shim(s) to achieve proper alignment.
7. Install shim(s) behind the backing plate and evenly torque hub bolts to manufacturer's specification.
8. Reinstall tire assembly and finish alignment.



95-296-0114

Fiat Rear Camber /Toe Shim pack

1. Perform pre-inspection, checking for loose or worn parts.
2. Perform complete alignment check to determine the alignment need.
3. Raise the rear of the vehicle and support securely.
4. Remove tire and wheel assembly.
5. Loosen the four wheel hub bolts.
6. Choose the correct option for camber/toe shim(s) to achieve proper alignment.
7. Install shim(s) behind the backing plate and evenly torque hub bolts to manufacturer's specification.
8. Reinstall tire assembly and finish alignment.



95-296-0114